



Main Specifications

Required fluids	Compressed air	Type	Clean air
		Pressure	0.45–0.5 MPa
		Required volume	180 L/min. (A.N.R)
	Cleaning water	Type	Purified water for industrial use
		Reservoir capacity	500 cc
		Required volume	240 cc/h
Diameters of connections	Compressed air supply port	HIGH COUPLER socket 30SM (plug on equipment side: 30PF)	
	Cleaning fluid drain	Hose nipple Rc1/4	
	Reservoir drain	Plug Rc1/8	
Input power supply	Voltage	100 VAC, single-phase	
	Plug	Japanese type(with earth)	
	Cable length	2 m	
	Power consumption	130 W	
Weight	Equipment weight	34 kg (when 500 cc of cleaning water is in the reservoir)	

Outer Dimensions



 **Nakamura** Nakamura Choko Co., Ltd.

MAC Center, 27-27 Tsuruta-cho, Nishi-ku, Sakai City, Osaka
593-8323 Japan

 +81-72-274-0777

 +81-72-273-3313

 nagai@nakamura-gp.co.jp (Person in charge: Mutsuo Nagai)

soga@nakamura-gp.co.jp (Person in charge: Takeshi Soga)

 <http://www.nakamura-gp.co.jp>

The Nakamura Choko Co., Ltd. factory has attained ISO14001 Environmental Management System and ISO9001 Quality Management System certifications.

Please be aware that the specifications and appearances of the products described in this catalog are subject to change without prior notice for the purpose of improvement.
Colors of actual products may differ slightly from those in the catalog, depending on printing conditions.

Contents of the catalog current as of May 2009

new

Cleaning with water and air

Automatic Nozzle Cleaner

MAC-III

